

TA-Modulator



Combined control & balancing valves

Pressure independent balancing and control valve for modulating control

TA-Modulator

The new uniquely shaped EQM characteristics provide highly precise temperature control. The valve is compatible with linear, proportional or 3-point actuators. A built-in differential pressure controller provides high control authority, control stability and automatic limitation of design flow. Measurement of flow and available pressure enables system optimisation and diagnostics.

Key features

- > **Precise temperature control**
Provide uniquely shaped EQM characteristic for best modulating control.
- > **Precise control**
Uniquely shaped EQM characteristic provides an up to 6 times larger operating stroke than linear valves.
- > **Quick hydronic balancing**
Automatic flow limitation when actuator is fully open protects entire system against overflows.
- > **Easy troubleshooting**
Flow and differential pressure measuring helps to reduce pump consumption and provides all necessary data for system diagnostics.



Technical description

Application:

Heating and cooling systems.

Functions:

Control EQM: DN 15-200 normal flow
Control LIN: DN 65-200 high flow
Pre-setting (max. flow)
Differential pressure control
Measuring (ΔH , t , q)
Isolation (for use during system maintenance – see “Leakage rate”)

Dimensions:

DN 15-200

Pressure class:

DN 15-50: PN 16
DN 65-200: PN 16, PN 25

Differential pressure (Δp_V):

Max. differential pressure ($\Delta p_{V_{max}}$):

DN 15-32: 600 kPa = 6 bar

DN 15-25: 400 kPa = 4 bar*

DN 40-50: 400 kPa = 4 bar

DN 65-200: 800 kPa = 8 bar

Min. differential pressure ($\Delta p_{V_{min}}$):

DN 15-20: 15 kPa = 0.15 bar

DN 25-32: 23 kPa = 0.23 bar

DN 40-200: 30 kPa = 0.30 bar

DN 65-80 HF: 45 kPa = 0.45 bar

DN 100-125 HF: 55 kPa = 0.55 bar

DN 150-200 HF: 60 kPa = 0.60 bar

(Valid for maximum setting, fully open.

Other settings will require lower differential

pressure, check with the software HySelect.)

$\Delta p_{V_{max}}$ = The maximum allowed pressure drop over the valve to fulfill all stated performances.

$\Delta p_{V_{min}}$ = The minimum recommended pressure drop over the valve, for proper differential pressure control.

*) With Δp insert in PPS.

HF = High flow

Flow range:

The flow (q_{max}) can be set within the range:

DN 15: 92 - 480 l/h

DN 20: 200 - 975 l/h

DN 25: 340 - 1750 l/h

DN 32: 720 - 3600 l/h

DN 40: 1000 - 6500 l/h

DN 50: 2150 - 11200 l/h

DN 65: 4150 - 24100 l/h

DN 65 HF: 7460 - 36500 l/h

DN 80: 5850 - 37300 l/h

DN 80 HF: 9520 - 49000 l/h

DN 100: 11700 - 51700 l/h

DN 100 HF: 18000 - 75900 l/h

DN 125: 15000 - 77300 l/h

DN 125 HF: 23300 - 127000 l/h

DN 150: 26100 - 126000 l/h

DN 150 HF: 38800 - 190000 l/h

DN 200: 35000 - 209000 l/h

DN 200 HF: 73200 - 329000 l/h

q_{max} = l/h at each setting and fully open valve plug.

HF = High flow

Temperature:

DN 15-32:
 Max. working temperature: 120°C
 Min. working temperature: -20°C
 DN 15-25 with Δp insert in PPS, DN 40-50:
 Max. working temperature: 90°C
 Min. working temperature: -10°C
 DN 65-200:
 Max. working temperature: 120°C
 Min. working temperature: -10°C

Media:

Water or neutral fluids, water-glycol mixtures (0-57%).

Lift:

DN 15-20: 4 mm
 DN 25-32: 6,5 mm
 DN 40-50: 15 mm
 DN 65-125: 20 mm
 DN 150: 30 mm
 DN 200: 32,5 mm

Rangeability:

DN 15-32: >75
 DN 40-80: >125
 DN 100-150: >150
 DN 100-150 HF: >125
 DN 200: >125
 DN 200 HF: >125

Leakage rate:

Leakage flow $\leq 0.01\%$ of max. $q_{\max}$ (max. setting) and correct flow direction. (Class IV according to EN 60534-4).

Characteristics:

Independent shaped EQM.
 DN 65-200 HF: Linear.

Material:

DN 15-32:
 Valve body: AMETAL®
 Valve insert: AMETAL® and PPS
 Valve plug: Brass CW724R (CuZn21Si3P)
 Spindle: Stainless steel
 Spindle seal: EPDM O-ring
 Δp insert: PPS and AMETAL® or PPS
 Membrane: EPDM
 Springs: Stainless steel
 O-rings: EPDM
 DN 40-50:

Valve body: AMETAL®
 Valve insert: AMETAL®
 Valve plug: AMETAL® and PTFE
 Spindle: Stainless steel
 Spindle seal: EPDM O-ring
 Δp insert: PPS
 Membrane: EPDM
 Springs: Stainless steel
 O-rings: EPDM
 DN 65-200:
 Valve body: Ductile iron EN-GJS-400-15
 Valve insert: Ductile iron EN-GJS-400-15 and brass
 Valve plug: Stainless steel and EPDM O-ring
 Valve seat: Stainless steel
 Spindle: Stainless steel
 Spindle seal: EPDM
 Δp insert: Ductile iron EN-GJS-400-15, stainless steel and brass.
 Membrane: Reinforced EPDM
 Springs: Stainless steel
 O-rings: EPDM

AMETAL® is the dezincification resistant alloy of IMI Hydronic Engineering.

Surface treatment:

DN 15-50: Non treated
 DN 65-200: Electrophoretic painting

Connection:

DN 15-50: External thread according to ISO 228.
 DN 65-200: Flanges according to EN-1092-2, type 21. Face to face length according to EN 558, series 1.

Connection to actuator:

DN 15-32: M30x1.5, push
 DN 40-50: M30x1.5, push/pull
 DN 65-200: 2xM8, push/pull

Actuators:

DN 15-20:
 TA-Slider 160, EMO TM, TA-TRI.
 DN 25-32:
 TA-Slider 160, TA-MC50-C*.
 DN 40-50:
 TA-Slider 500, TA-Slider 750*.
 DN 65-125:
 TA-Slider 750.
 DN 100-125 HF:
 TA-Slider 750 $\Delta pV \leq 4$ bar,
 TA-Slider 1600 $\Delta pV \leq 8$ bar.
 DN 150-200, DN 150-200 HF:
 TA-Slider 1600.

TA-Slider 160, 500, 750 and 1600 also available with fail-safe function.

*) Adapter to be ordered separately, see "Adapters for actuators".

For more details on actuators, see separate technical leaflets.


Certification and directives:

DN 65-200: CE, EAC, UKCA


Valve characteristics

Nominal valve characteristic for all settings

EQM




LIN




Measuring accuracy

Maximum flow deviation at different settings

DN 15-32 (1/2"-1 1/4")



DN 40-200 (1 1/2"-8")



*) Setting (%) of fully open valve.

Correction factors

The flow calculations are valid for water (+20°C). For other liquids with approximately the same viscosity as water (≤ 20 cSt = 3°E = 100S.U.), it is only necessary to compensate for the specific density. However, at low temperatures, the viscosity increases and laminar flow may occur in the valves. This causes a flow deviation that increases with small valves, low settings and low differential pressures. Correction for this deviation can be made with the software HySelect or directly in our balancing instruments.

Noise

Performance of the valves is subject to water quality being of an appropriate regional standard (including particulate and free, entrained and dissolved gases compliant with VDI 2035), failure to do so can result in shortened life span, reduced controllability and noise.

Actuators

The valve is developed to work together with recommended actuators according to table. Care should be taken by the user to ensure that actuators not manufactured by IMI Hydronic Engineering are fully compatible to provide optimal control from the valve. Failure to do so may provide unsatisfactory results.

See separate catalogue leaflets for more details about the actuators.

Push actuators of other brands require;

Working range


DN 15-20: X (closed - fully open) = 11.6 - 15.85

DN 25-32: X (closed - fully open) = 10.1 - 16.85

Closing force

DN 15-20: Min. 125 N (max. 500 N)

DN 25-32: Min. 190 N (max. 500 N)



Maximum recommended pressure drop (ΔpV) for valve and actuator combination

The maximum recommended pressure drop over a valve and actuator combination for close off (ΔpV_{close}) and to fulfill all stated performances (ΔpV_{max}).

DN	EMO TM	TA-TRI	TA-Slider 160	TA-MC50-C	TA-Slider 500	TA-Slider 750	TA-Slider 1600
	[kPa]	[kPa]	[kPa]	[kPa]	[kPa]	[kPa]	[kPa]
15	400/600	400/600	400/600	-	-	-	-
20	400/600	400/600	400/600	-	-	-	-
25	-	-	400/600	400/600	-	-	-
32	-	-	600	600	-	-	-
40	-	-	-	-	400	400	-
50	-	-	-	-	400	400	-
65	-	-	-	-	-	800	-
65 HF	-	-	-	-	-	800	-
80	-	-	-	-	-	800	-
80 HF	-	-	-	-	-	800	-
100	-	-	-	-	-	800	-
100 HF	-	-	-	-	-	400	800
125	-	-	-	-	-	800	-
125 HF	-	-	-	-	-	400	800
150	-	-	-	-	-	-	800
150 HF	-	-	-	-	-	-	800
200	-	-	-	-	-	-	800
200 HF	-	-	-	-	-	-	800
Closing force	125 N	200 N	190 N	500 N	500 N	750 N	1600 N

TA-Slider 160, 500, 750 and 1600 also available with fail-safe function.

ΔpV_{close} = The maximum pressure drop that the valve can close against from an opened position, with a specified force (actuator) without exceeding stated leakage rate.

ΔpV_{max} = The maximum allowed pressure drop over the valve to fulfill all stated performances.

HF = High flow

Sizing

1. Choose the smallest valve size that can obtain the design flow with some safety margin, see “ $q_{\max}$ values”. The setting should be as open as possible.
2. Check that the available Δp_V is within the working range according to the valve size and variant.

$q_{\max}$ values

DN	Position									
	1	2	3	4	5	6	7	8	9	10
15	92	114	140	170	210	265	325	390	445	480
20	200	260	360	460	565	670	770	850	920	975
25	340	440	600	810	1010	1200	1350	1520	1640	1750
32	720	960	1350	1750	2150	2530	2850	3130	3380	3600

DN	Position												
	0.8	0.9	1.0	1.1	1.2	1.3	1.4	1.5	1.6	1.7	1.8	1.9	2.0
40	1000	1240	1530	1840	2200	2570	3020	3450	3960	4550	5200	5800	6500
50	2150	2640	3220	3790	4430	5150	5990	6870	7800	8790	9740	10600	11200

DN	Position												
	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00
65	-	-	4150	5100	6230	7700	9450	11500	13500	16100	19000	21800	24100
80	-	-	5850	7300	9180	12200	15500	19100	22800	26300	30000	33600	37300
100	11700	14100	16800	19700	22900	26400	30200	34200	38300	42400	46300	49500	51700
125	15000	18800	22800	27400	32100	37100	42400	47700	53400	59100	64700	71000	77300

DN	Position															
	1.25	1.50	1.75	2.00	2.25	2.50	2.75	3.00	3.25	3.50	3.75	4.00	4.25	4.50	4.75	5.00
65 HF	7460	9580	11590	13550	15490	17540	19620	21760	23860	25610	27950	29840	31250	33300	34750	36500
80 HF	9520	12080	14600	17050	19520	21970	24390	26860	29420	32280	34700	37260	40260	42860	44970	49000
100 HF	18000	22600	27000	31200	35300	39300	43400	47500	51600	55700	59700	63600	67300	70700	73600	75900
125 HF	23300	30000	36500	43200	49600	55800	62700	69700	76500	83500	90900	98900	105000	112000	119000	127000

DN	Position																
	5.0	5.5	6.0	6.5	7.0	7.5	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	12.5	13.0
150	26100	30900	36100	41500	48400	54300	61700	69300	76500	86000	95000	103000	112000	120000	126000	-	-
200	35000	43800	54000	64900	77700	90700	106000	119000	132000	145000	158000	170000	183000	191000	200000	204000	209000


DN	Position										
	2.5	3.0	3.5	4.0	4.5	5.0	5.5	6.0	6.5	7.0	7.5
150 HF	38800	47400	54500	62500	70700	78700	86400	94000	102000	109000	117000
200 HF	-	-	73200	89000	105000	120000	136000	152000	168000	184000	201000
DN	Position										
	8.0	8.5	9.0	9.5	10.0	10.5	11.0	11.5	12.0	12.5	13.0
150 HF	123000	131000	139000	146000	154000	162000	171000	179000	190000	-	-
200 HF	217000	233000	250000	265000	276000	286000	295000	301000	310000	318000	329000

$q_{\max}$ = l/h at each setting and fully open valve plug.
HF = High flow


Installation

Flow direction


DN 15-32



DN 40-50




DN 65-200



Ingress protection

EMO TM / TA-TRI / TA-Slider 160 / TA-Slider 500 / TA-Slider 750 / TA-Slider 1600




IP54



IP54




IP54



IP54

TA-MC50-C




IP40



IP40



IP40




IP40


Installation of actuator

Note: Free space is required above the actuator for easy mounting/dismounting.


EMO TM




TA-Slider 160 *




TA-TRI




TA-MC50-C



TA-Slider 500 *




TA-Slider 750/1600 / TA-Slider 750/1600 Plus, Fail-Safe Plus




*) Height depending on actuator version.

Application example




Operating function DN 15-32

Setting



1. Remove the installed actuator.
2. Turn the setting wheel to desired value, e.g. 5.0.

Isolation




1. Remove the installed actuator.
2. Turn the setting wheel clockwise to X.

Measuring q

1. Remove the installed actuator.
2. Connect the TA balancing instrument to the measuring points.
3. Input the valve type, size and setting and the actual flow is displayed.

Measuring ΔH



1. Remove the installed actuator.
2. Close the valve according to "Isolation".
3. Bypass the Δp -part by opening the ΔH spindle (red measuring point) ~1 turn **anticlockwise**, with a 5 mm Allen key.
4. Connect the TA balancing instrument to the measuring points and measure.

Important! After the measurement is completed;
5. Close the ΔH spindle (red measuring point) **clockwise** to stop.


6. Reopen the valve to previous setting.

Measuring temperature

For temperature measurement the **red** measuring point is recommended.


Operating function DN 40-50

Setting



1. Remove the installed actuator.
2. Turn the setting wheel to desired value, e.g. 1.3.

Isolation




1. Remove the installed actuator.
2. Turn the setting wheel clockwise to stop (position 0 ± 0.3).

Measuring q

1. Remove the installed actuator.
2. Connect the TA balancing instrument to the measuring points.
3. Input the valve type, size and setting and the actual flow is displayed.

Measuring ΔH



1. Remove the installed actuator.
2. Close the valve according to "Isolation".
3. Deactivate the Δp -part by closing the ΔH spindle (red measuring point) **clockwise** to stop, with a 5 mm Allen key.
4. Open the venting screw ~1 turn for 5 seconds and then close it (some water leakage can occur).
5. Connect the TA balancing instrument to the measuring points and measure.

Important! After the measurement is completed;


6. Activate the Δp -part by opening the ΔH spindle (red measuring point) **anticlockwise** to stop.
7. Reopen the valve to previous setting.

Measuring temperature

For temperature measurement the **red** measuring point is recommended.


Operating function DN 65-200

Setting



1. Disengage the actuator from the valve spindle.
2. Turn the setting wheel to desired value, e.g. 2.4.

Isolation




1. Disengage the actuator from the valve spindle.
2. Turn the setting wheel clockwise to stop (position 0 ± 0.5).

Measuring q

1. Disengage the actuator from the valve spindle.
2. Connect the TA balancing instrument to the **red** and **blue** measuring points.
3. Input the valve type, size and setting and the actual flow is displayed.

Measuring ΔH




1. Disengage the actuator from the valve spindle.
2. Close the valve according to "Isolation".
3. Connect the TA balancing instrument to the **red** and **black** measuring points and measure.

Important! After the measurement is completed;
4. Reopen the valve to previous setting


Measuring temperature

For temperature measurement the **black** measuring point is recommended.

Secure the setting position (optionally)




Articles



DN 15-32 HP – Temperature -20 – +120°C, ΔpV max. 600 kPa

External threads according to ISO 228.


DN	d	L	H1	H2	W	q _{max} [l/h]	Kg	EAN	Article No
15	G3/4	74	55	55	54	480	0,60	7318794033405	52 164-415
20	G1	85	64	55	64	975	0,75	7318794033504	52 164-420
25	G1 1/4	93	64	67	64	1750	0,90	7318794033603	52 164-425
32	G1 1/2	117	78	70	78	3600	1,5	7318794027305	52 164-332



DN 15-25 – Temperature -10 – +90°C, ΔpV max. 400 kPa

External threads according to ISO 228.

DN	d	L	H1	H2	W	q _{max} [l/h]	Kg	EAN	Article No
15	G3/4	74	55	55	54	480	0,54	7318794027008	52 164-315
20	G1	85	64	55	64	975	0,69	7318794027107	52 164-320
25	G1 1/4	93	64	67	64	1750	0,79	7318794027206	52 164-325




DN 40-50 – Temperature -10 – +90°C, ΔpV max. 400 kPa

External threads according to ISO 228.

DN	d	L	H	W	q _{max} [l/h]	Kg	EAN	Article No
40	G2	187	132	88	6500	3,5	7318794030602	52 164-340
50	G2 1/2	196	135	88	11200	3,9	7318794030701	52 164-350

*) Connection to actuator.

→ = Flow direction

**DN 65-200 – Temperature -10 – +120°C, ΔpV max. 800 kPa**

Flanges according to EN-1092-2, type 21.

PN 16

DN	Number of bolt holes	ØD	L	H	q _{max} [m³/h]	Kg	EAN	Article No
65	4	185	290	249	24,1	18	3831112533271	322021-11001
65 HF	4	185	290	249	36,5	18	5902276810213	322021-11008
80	8	200	310	260	37,3	22	3831112533318	322021-11101
80 HF	8	200	310	260	49,0	22	5902276810251	322021-11109
100	8	220	350	280	51,7	33	3831112535527	322021-11200
100 HF	8	220	350	280	75,9	33	3831112535565	322021-11203
125	8	250	400	287	77,3	45	3831112535602	322021-11300
125 HF	8	250	400	287	127	45	3831112535640	322021-11303
150	8	285	480	357	126	75	3831112535701	322021-11400
150 HF	8	285	480	357	190	75	3831112535749	322021-11403
200	12	340	600	391	209	136	5902276819810	322021-11500
200 HF	12	340	600	391	329	136	5902276819827	322021-11503

PN 25



DN	Number of bolt holes	ØD	L	H	q _{max} [m³/h]	Kg	EAN	Article No
65	8	185	290	249	24,1	18	3831112533288	322021-11002
65 HF	8	185	290	249	36,5	18	5902276810220	322021-11009
80	8	200	310	260	37,3	22	3831112533325	322021-11102
80 HF	8	200	310	260	49,0	22	5902276810268	322021-11110
100	8	235	350	280	51,7	34	3831112535534	322021-11201
100 HF	8	235	350	280	75,9	34	3831112535572	322021-11204
125	8	270	400	287	77,3	47	3831112535619	322021-11301
125 HF	8	270	400	287	127	47	3831112535657	322021-11304
150	8	300	480	357	126	77	3831112535718	322021-11401
150 HF	8	300	480	357	190	77	3831112535756	322021-11404
200	12	360	600	391	209	136	5902276819834	322021-11501
200 HF	12	360	600	391	329	136	5902276819841	322021-11504

HF = High flow

*) Connection to actuator.

→ = Flow direction

Connections




With internal thread

Threads according to ISO 228. Thread length according to ISO 7-1.

Swivelling nut.

Brass/AMETAL®

For DN	D	D1	L*	EAN	Article No
15	G3/4	G1/2	21	7318794016903	52 163-015
20	G1	G3/4	23	7318794017009	52 163-020
25	G1 1/4	G1	23	7318794017108	52 163-025
32	G1 1/2	G1 1/4	31	7318794017207	52 163-032
40	G2	G1 1/2	30	7318794032705	52 163-040
50	G2 1/2	G2	32	7318794032804	52 163-050




With external thread

Threads according to ISO 7-1.

Swivelling nut.

Brass

For DN	D	D1	L*	EAN	Article No
15	G3/4	R1/2	29	4024052516612	0601-02.350
20	G1	R3/4	32,5	4024052516810	0601-03.350
25	G1 1/4	R1	35	4024052517015	0601-04.350
32	G1 1/2	R1 1/4	38,5	4024052517213	0601-05.350




Welding connection

Swivelling nut.

Brass/Steel 1.0045 (EN 10025-2)

For DN	D	Pipe Ø	L*	EAN	Article No
15	G3/4	15	36	7318792748509	52 009-015
20	G1	20	40	7318792748608	52 009-020
25	G1 1/4	25	40	7318792748707	52 009-025
32	G1 1/2	32	40	7318792748806	52 009-032
40	G2	40	45	7318792748905	52 009-040
50	G2 1/2	50	50	7318792749001	52 009-050




Soldering connection

Swivelling nut.

Brass/gunmetal CC491K (EN 1982)

For DN	D	Pipe Ø	L*	EAN	Article No
15	G3/4	15	13	7318792749308	52 009-515
15	G3/4	16	13	7318792749407	52 009-516
20	G1	18	15	7318792749506	52 009-518
20	G1	22	18	7318792749605	52 009-522
25	G1 1/4	28	21	7318792749704	52 009-528
32	G1 1/2	35	26	7318792749803	52 009-535
40	G2	42	30	7318792749902	52 009-542
50	G2 1/2	54	35	7318792750007	52 009-554

*) Fitting length (from the gasket surface to the end of the connection).


**Connection with smooth end**

For connection with press coupling.

Swivelling nut.

Brass/AMETAL®

For DN	D	Pipe Ø	L*	EAN	Article No
15	G3/4	15	39	7318793810601	52 009-315
20	G1	18	44	7318793810700	52 009-318
20	G1	22	48	7318793810809	52 009-322
25	G1 1/4	28	53	7318793810908	52 009-328
32	G1 1/2	35	59	7318793811004	52 009-335
40	G2	42	70	7318793811103	52 009-342
50	G2 1/2	54	80	7318793811202	52 009-354

**Compression connection**

Support bushes shall be used, for more information see catalogue leaflet FPL.

Should not be used with PEX pipes.

Brass/AMETAL®

Chrome plated

For DN	D	Pipe Ø	L**	EAN	Article No
15	G3/4	15	27	7318793705006	53 319-615
15	G3/4	18	27	7318793705105	53 319-618
15	G3/4	22	27	7318793705204	53 319-622

*) Fitting length (from the gasket surface to the end of the connection).

**) Over all length L refers to unassembled coupling.


Adapters for actuators

Adapters

Adapters to other combinations of valve and recommended actuator are NOT needed.

For actuator	For DN	EAN	Article No
TA-MC50-C	25-32	3831112533851	322042-10700
TA-Slider 750	40-50	5902276819308	322042-80800


Accessories



Grip for setting wheel, optional

For better grip when presetting.
For TA-COMPACT-P/-DP and TA-Modulator (DN 15-32).


Colour	EAN	Article No
Orange	7318794040502	52 164-950



Protection cap

For TA-COMPACT-P/-DP, TA-Modulator (DN 15-20), TBV-C/-CM.

Colour	EAN	Article No
Red	7318793961105	52 143-100





Tamper proof cover

Set containing plastic cover and locking ring for valves with connection M30x1.5 to thermostatic head/actuator.

Prevents manipulation of setting.

Suitable for DN 15-32.

	EAN	Article No
	7318794030206	52 164-100



Insulation

For heating/comfort cooling.

Material: EPP.

Fire class:

DN 15-32: E (EN 13501-1), B2 (DIN 4102).


DN 40-50: F (EN 13501-1), B3 (DIN 4102).

For DN	L	H1	H2	D	EAN	Article No
15	100	61	71	84	7318794027404	52 164-901
20	118	67	79	90	7318794027503	52 164-902
25	127	71	84	104	7318794027602	52 164-903
32	154	85	99	124	7318794027701	52 164-904
40	277	105	-	131	7318794030800	52 164-905
50	277	105	-	131	7318794030909	52 164-906


Spindle extension for DN 15-20

Recommended together with the insulation to minimize the risk of condensation at the valve-actuator interface.

M30x1,5.



Type	L	EAN	Article No
Plastic, black	30	4024052165018	2002-30.700


**Measuring point, extension 60 mm**

Can be installed without draining of the system.

AMETAL®/Stainless steel/EPDM

For all dimensions.

L	EAN	Article No
60	7318792812804	52 179-006

**Venting extension**

Suitable when insulation is used.

AMETAL®

For DN	D	d	H	EAN	Article No
40-50	M10x1	M10x1	32	7318794033702	52 164-301

**Venting plug**

Spare part.

AMETAL®

For DN	EAN	Article No
40-50	7318794033801	52 164-302