ACCESSORIES

Shut-off cocks DIN 16 260, DIN 16 262 DIN 16 263, DIN 16 270, DIN 16 271, DIN 16 272





It is principle appropriate to install a barricade between the pressure measuring instrument and pressure pipe. Shut-off cocks make it possible to control or exchange a pressure measuring instrument without a breakdown. For shut-off cocks with a test connection, it is possible to connect an additional test pressure measuring instrument.

| Shut-off cock Female - Female | | | | | | | | |
|-------------------------------|--------|--------|-----------|----------|--------|----------|--|--|
| | Female | Female | PN in bar | Material | Female | Item no. | | |
| | G 1/2 | G 1/2 | 16 | Brass | Brass | 51 15 1 | | |
| | | | | | | | | |

| Shut-off cock Female - Male, DIN 16 261-B | | | | | | | | | |
|-------------------------------------------|--------|-------|-----------|-----------------|--------|----------|--|--|--|
| | Female | Male | PN in bar | Material | Female | Item no. | | | |
| H | G 1/4 | G 1/4 | 6 | В | Brass | | | | |
| | G 1/4 | G 1/4 | 6 | Stainless steel | | 56 06 3 | | | |
| | G 1/2 | G 1/2 | 25 | В | ass | 56 15 1 | | | |

| Shut-of cock Female - Female, G 1/2 with gland, G 1/4 without gland | | | | | | | |
|---------------------------------------------------------------------|--------|--------|-----------|----------|--------|----------|--|
| | Female | Female | PN in bar | Material | Female | Item no. | |
| | G 1/4 | G 1/4 | 16 | Brass | Brass | 52 06 1 | |
| | G 1/2 | G 1/2 | | Diass | | 52 15 1 | |

| Shut-off cock Union nut - Male according to DIN 16 260 and DIN 16 262 | | | | | | | | |
|-----------------------------------------------------------------------|-----------|---------|-----------|----------|-----------|----------|--|--|
| | Union nut | Male | PN in bar | Material | Union nut | Item no. | | |
| | G 1/4 | G 1/4 | 6 | Brass | Brass | 57 06 1 | | |
| | G 1/2 | G 1/2 | 25 | | | 57 15 1 | | |
| | M20x1,5 | M20x1,5 | 25 | | | 57 17 1 | | |
| | G 1/2 | G 1/2 | 25 | | Stainless | 57 15 3 | | |
| | M20x1,5 | M20x1,5 | 25 | 1.4571 | steel | 57 17 3 | | |

| Shut-off cock Union nut - Male, with test connection M20x1,5, DIN 16 263 | | | | | | | |
|--------------------------------------------------------------------------|-----------|---------|-----------|-----------------|--------------------|----------|--|
| | Union nut | Male | PN in bar | Material | Union nut | Item no. | |
| | G 1/2 | G 1/2 | 25 | Brass 1.4571 | Brass | 35 15 1 | |
| | M20x1,5 | M20x1,5 | | | | 35 17 1 | |
| | G 1/2 | G 1/2 | | | Stainless steel | 35 15 3 | |
| | M20x1,5 | M20x1,5 | | | | 35 17 3 | |

Shut-off cock Female - Female, with test flange



| Female | Female | PN in bar | Material | Female | Item no. |
|--------|--------|-----------|----------|--------|----------|
| G 1/2 | G 1/2 | 25 | Brass | Brass | 30 15 1 |
| | | | | | |

| Shut-off cock Loose nut - Male, with test flange 60x25 mm, DIN 16 263 | | | | | | | |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------|-------|-----------|----------|-----------|----------|--|
| | Loose nut | Male | PN in bar | Material | Loose nut | Item no. | |
| | G 1/2 | G 1/2 | 25 | Brass | Brass | 53 15 1 | |
| THE STATE OF THE S | | | | | | | |

| Shut-off cock Female - Rotatable Female | | | | | | | | |
|-----------------------------------------|--------|---------------------|-----------|----------|---------|----------|--|--|
| | Female | rotatable Female | PN in bar | Material | Females | Item no. | | |
| | G 1/2 | G 1/2 | 16 | Brass | Brass | 54 15 1 | | |

| Shut-off cock Female - Female, similiar to DIN 16 261 | | | | | | | | |
|-------------------------------------------------------|--------|--------|-----------|----------|--------|----------|--|--|
| | Female | Female | PN in bar | Material | Female | Item no. | | |
| | G 1/2 | G 1/2 | 16 | Brass | Brass | 55 15 1 | | |
| | | | | | | | | |